

## AMF Reece Button Wrapping & Knotting Machine



Better Shanks
Better Garments



## **BSW Mark II**

Applications of the BSW-Mark II button shank wrapper include suit jackets and outwear or any garment requiring a shank button.

## **Features**

Uses normal thread, which eliminates color matching issues as well as the need to buy expensive, special thread.

Suitable for any types and sizes of buttons.

Quick set up by user - friendly LCD monitor.

Perfect thread trimming with a knife.

Tight knotting preventing the button from being detached.

No needle or bobbin required.

Simple adjustment between flat and shank buttons on the control panel.


Number of wraps and knots per shank can be programmed.

Productivity of 4,000 buttons per 8-hour shift on average.

Technical Specifications BSW MarkII	
Number of Wrapping	1 - 130
Number of Knotting	1 - 10
Shank Height	1 - 10 mm
Electrical Requirements	100 - 240 V, 50/60 Hz, 1Ph
Air Requirements	5.5 bar (80 psi), 14 l/m (0.5 cfm)
Machine Dimensions Weight	400 mm (L) x 400 mm (W) x 350 mm (H) 19 kg
Crated Dimensions Weight	370 mm (L) x 440 mm (W) x 380 mm (H) 20 kg

Accuracy of illustration and description of equipment shown herein apply to products as manufactured at time of publication.






Types of wrapping and knotting




Control panel



Maximum button size









World Headquarters Prostejov, Czech Republic

Phone: 420 582 309 140
Fax: 420 582 360 606
E-mail: amfreece@amfreece.cz

Southewest Asia Istanbul, Turkey
Phone: 90.212.465.0707

Fax: 90.212.465.0711 E-mail: amfreeceturkey@superonline.com

E-Mail: marketing@amfreece.com Website: www.amfreece.com